

## UPGROWTH OF STRONG INDUCED TECTONIC EARTHQUAKES IN CONDITIONS OF TECHNOGENIC LOADING ACCUMULATION

V. V. Adushkin

Institute of Geosphere Dynamics (IDG RAS)

[adushkin@idg.chph.ras.ru](mailto:adushkin@idg.chph.ras.ru)

Technogenic or induced seismicity, actively evolving in conditions of intensive technogenesis, closely related to the natural tectonic seismicity. Its joint evolving and interaction presents actual scientific and technology problem due to the initiation of strong technogenou-tectonic earthquakes by means of trigger releasing of natural tectonic strains under the influence of rising external loading on geological medium.

Results of zoning of European part of Russia territory on intensity of seismic oscillation induced by mining operations and occurred due to mass explosions are presented in the paper. Analysis of upgrowth of technogenic-induced seismicity of Kuzbass territory, intensive rise of that begins in 70<sup>th</sup>-80<sup>th</sup> of the last century and finalized in conditions of permanently growing thechnogenous loading by Bochata catastrophic earthquake of 18 June 2013 (M=5.8-6.1), are presented in the paper too. This earthquake is happened to be the most large technogenous seismic event in conditions of mining of solid commercial minerals [Emanov et al., 2014]. Ground motion intensity in the epicenter was 7 and buildings were destroyed in the nearest cities and villages. Cities Prokopievsk, Kisilevsk, Novokuznetsk were covered by intensity of 4, and Novosibirsk and Barnaul located on the distance of 200 km were landed in 2 on Richter scale zone.

During industrialization of Kuzbass, which territory accommodate of huge stocks (about 700 billion tones) of high quality coal, technogenic loading by means of intensive underground and open-pit coal-mining was rising. Today it is executing at 52 excavating plants and 60 large mines reaching to 300 million tons per year. As it follows from the presented information permanent rise of the number and the intensity seismic events are registered simultaneously with the yearly dilation of mine explosive works. The main opinion is devoted to the upgrowth of strong thechnogenic-tectonic earthquakees of trigger character having energetic scale of  $K > 8.5-9$  and magnitude of  $M > 3$  consequently. Sources of such kind of earthquakes occur in a rock massif under changes of geomechanic and hydrologic regimes and correspond to restructuring of stress strain behavior under thechnogenic loading.

Presented information shows the confidence and relatively fast grows of technogenic loading in the period before 2000. An example the blaster agent demand for the last 10 years was grown from 100-200 thousand ton/yr to several billions ton/yr. More than that the intensive grow of plaster agent demand supplementary rises thechnogenic loading on the crust interior creating the flow of seismic energy  $10^{13}-10^{14}$  J/yr and the energy of influence at the level of 1.5 mW.

The similar grow of thechnogenic loading in combination with the natural seismic activity was accorded by the rise of the number of induced earthquakes which includes the seismogenou-tectonic ones. By reference to seismic catalogues of Altay-Sayan region [Yakovlav et al., 2013] and analysis of the International Seismological Centre (ISC) catalogues [Adushkin, 2015 ] succeed to reveal that for the period of 1963-2005 at Kuzbass territory have occurred approximately 1-2 technogenou-tectonic earthquakes  $M=3.5-4$  per year. Its number was grows confidently to 10-20 events  $M=4-5$  per year in the period of intensive output increase after 2006.

Mentioned rise of similar strong earthquakes was finalized by the catastrophic Bachat earthquake= $5.8-6.1$  and sours depth 2-14 km in the Bachat mining plant.

The study is performed under the financial support of the Russian Scientific Fund project No 16-17-00095.

### References

1. A. F. Emanov, A. A. Emanov, A. V. Fateev, E. V. Leskova, E. V. Shevkunova, and V. G. Podkorytova. MINING-INDUCED SEISMICITY AT OPEN PIT MINES IN KUZBASS (BACHATSKY EARTHQUAKE ON JUNE 18, 2013) // Journal of Mining Science, 2014, Vol. 50, No 2, P. 41-46
2. D. V. Yakovlev, T. I. Lazarevich, and S. V. Tsirel'. NATURAL AND INDUCED SEISMIC ACTIVITY IN KUZBASS // Journal of Mining Science, 2013, Vol. 49, No 6, P. 20-34
3. Adushkin V. V. Triggered seismicity in Kuzbass // Trigger effects in geosystems: Proceedings of the 3<sup>rd</sup> All-Russian workshop. Moscow: GEOS, 2015, P.8-29 Rus

ANALYSIS OF DATA ON THE MANIFESTATION OF EXTREME EVENTS DURING  
DEVELOPMENT OF MINERAL RESOURCES AND THEIR RELATIONSHIP WITH  
THE DYNAMICS OF THE BLOCKS OF THE EARTH CRUST

*A. S. Batugin<sup>1</sup>, I. M. Batugina<sup>1</sup>*

<sup>1</sup> National University of Science and Technology "MISIS"(NUST «MISiS» MMI)

[as-bat@mail.ru](mailto:as-bat@mail.ru)

Developed in Russia the method of geodynamic zoning sequentially includes identifying of hierarchical block structure of the crust of region reclamation of mineral resources or earth surface, estimating of the dynamic interaction between blocks, assessing the state of stress of blocks, developing recommendations for hazard reduction. Analysis of the data obtained during the elaboration of the dozens geodynamic zoning projects in different areas shows there is relationship on the one hand between locations of extreme events, especially rock bursts and tectonic rock bursts, earthquakes in case of flooding of mines, accidents on engineering nets and secondly geodynamic danger zones formed by the interaction of the Earth blocks crust.

References

1. Batugina I. M., Petukhov I. M. Geodynamic zoning of mineral deposits for planning and exploitation of mines. Oxford & IBH Publishing Co. Pvt. Ltd. New Delhi. 1990. 159 p.
2. Batugin A. S., Batugina I. M., Lan Tianwei Tectonophysical model of fault tectonic rock burst with wing sliding//Journal of Liaoning Technical University. Natural Science. 2016. Vol.35, №6, p. 561-565.

STUDY OF ROCK SAMPLES USING LASER ULTRASONIC STRUCTUROSCOPY AND  
TOMOGRAPHY

*A. S. Bychkov, A. A. Karabutov, E. B. Cherepetskaya, N. A. Morozov*

Mining Institute, National University of Science and Technology MISIS (NUST MISIS,  
Russia)

[abychkov@optoacoustic.ru](mailto:abychkov@optoacoustic.ru)

A successful geoinformation system should include a digital geomechanical model that preserves the structural features of a mineral deposit and the physico-mechanical properties of rocks. It is proposed that laser ultrasonic structuroscopy and tomography should be used to study the internal structure, porosity, and microcracks of rock samples as well as to evaluate the local elastic modulus of geomaterials. Ultrasonic wave is excited by a short laser pulse absorbed by the near-surface layer. Specially developed wideband piezoelectric transducers are used to record transmitted and scattered acoustic signals, providing information on the internal structure of geomaterials. Unlike conventional ultrasonic methods, the proposed technique employs a laser source to excite powerful wideband ultrasonic pulses in the frequency range 300 kHz to 10 MHz, with the pressure amplitude reaching 0.5 MPa. Thus, pores, microcracks, and high- and low-density heterogeneities 100microns to 1cm in size can be detected in rock samples 2mm to 4cm thick. Laser-based excitation of ultrasonic signals and the registration of scattered ultrasonic waves by a piezoelectric transducer array enable 3D imaging of the internal structure of rock samples.

This work was conducted under Grant No.16-17-10181 of the Russian Science Foundation.

DEVELOPMENT AND UTILIZATION OF NEW GEOINFORMATIC ROCK ARRAY  
STRUCTURE AND PROPERTIES PREDICTION TECHNOLOGIES

*V. N. Zakharov<sup>1</sup>, A. G. Chernikov<sup>1</sup>, O. N. Malinnikova<sup>1</sup>, Y. S. Isaev<sup>2</sup>*

<sup>1</sup> Institute of Comprehensive Exploitation of Mineral Resources  
Russian Academy of Sciences (IPKON RAS),

<sup>2</sup> Open Joint Stock Company Scientific, Research, Design and Surveying Institute  
«Lenmetrogiprotrans»

[olga\\_malinnikova@mail.ru](mailto:olga_malinnikova@mail.ru)

In order to predict the depth structure and properties of a rock array, a Markov tomography method has been developed that uses the results of remotely-measured areal topography changes of the Earth's surface and geologo-geophysical fields. The method, the mathematical foundation of which is the Markov finite chain theory, is based on the probabilistic inheritance of the Markov properties of depth deposits assumption by the overlaying beddings. The prognostic structure and properties of the subsurface deposits model has been calculated in the solution of the inverse problem, using computer analysis of the geologo-geophysical fields measured on the rock array surface.

The method has been proved as a program methodological complex that provides for rapid processing, interpretation, and 3D modeling of the structure and properties of arbitrary-genesis objects being studied.

The developed method has been successfully tested when conducting surface engineering and geological research on the areas of subterranean transportation and coal-methane facilities under construction that are subject to be built in rough terrain conditions, where the efficiency of surface geophysical methods application has proved to be insufficient. In this report, the efficiency of the method being proposed has been demonstrated using the Krasnaya Polyana area survey example.

Today, the issue of aggregating the developed method with the geodynamic zoning technology using satellite photographs lineament analysis data is being developed in order to increase the efficiency of remote prediction of subsurface deposits structure and properties.

## SUPPORT PRESSURE ANALYSIS IN SWELLING ROCK

*R. Doostmohammadi*

Mining Engineering Department, University of Zanjan, Zanjan ( Iran)

[ramin.doostmohammadi@znu.ac.ir](mailto:ramin.doostmohammadi@znu.ac.ir)

Excavating in swelling rock presents some special challenges to geotechnical engineers since misjudgments in the design of support systems can lead to very costly failures. In order to understand the issues involved in the process of designing support for this type of excavation, it is necessary to examine some concepts of how a rock mass surrounding an excavation swells and how the support systems act to control this swelling deformation. Given the above, determining the induced pressure in support systems has a particular importance. In this study, we try to examine the ability of artificial neural network in combination of leave one out technique to predict the support final pressure under various initial stresses in swelling rock. The result shows that proposed method can be introduced as a suitable tool for prediction the nonlinear support pressure in swellable rock with acceptable accuracy.

### References

1. Aksoy, C. O., Ogul, K., Topal, L., Ozer, S. C., Ozacar, V., Posluk, E. Numerical modeling of non-deformable support in swelling and squeezing rock. *International Journal of Rock Mechanics and Mining Sciences* 52. 2012. P.61-70.
2. Butscher, C., Huggenberger, P., Zechner, E., Einstein, H. H. Relation between hydrogeological setting and swelling potential of clay-sulfate rocks in tunneling, *Engineering Geology* 122. 2011. P.204-214.
3. Doostmohammadi, R., Moosavi, M., Mutschler, Th., Osan, C. Influence of cyclic wetting and drying on swelling behavior of marlstone in south west of Iran. *Environmental Geology* 58. 2009. P.999-1009.
4. Zurada, J. M. *Introduction to artificial neural system*. West publishing company. 1992. 683pp.

GEOINFORMATIONAL SUPPORT OF ESTIMATES AND FORECAST HAZARDOUS  
NATURAL PROCESSES IN MINING COAL SEAMS

Kolikov K. S., Egorova E. A.

National University of Science and Technology "MISiS" (NUST "MISiS", Russia)

[kolikovks@mail.ru](mailto:kolikovks@mail.ru)

After the restructuring of the coal industry's spread widely coal face operations of coal seams on a "mine - long wall face". In addition to using high-performance equipment this led to a considerable reduction of exploited and reserve mining sites. In these conditions cardinally increases requirements for safe and efficient coal mining. One of the main problems in this direction is the identification of abnormal areas of the stress-strain state of coal rock mass. A special role is this question is in making preparations mines in outburst hazard coal seams.

Forecast anomalous zones can be done through the creation of an information model of the geological object, which allows systematize and process the scattered data about the subject and to consider it entirely or any fragment.

Detection anomalous zones allows to select mining sites hazardous gas-and-dynamic phenomena increased permeability zone, and as a result of increased gas emission, it is necessary to take into account both in the planning of mining works as well as in the degassing of coal development preparation.

GEOINFORMATION MONITORING OF GEODYNAMIC AND GAS-DYNAMIC STATE  
OF THE ROCK MASS.

*S. S. Kubrin<sup>1</sup>, E. I. Zhuravlev<sup>1</sup>*

<sup>1</sup> Institute of Comprehensive Exploitation of Mineral Resources Russian Academy of Sciences  
(IPKON RAS, Russia)

[s\\_kubrin@mail.ru](mailto:s_kubrin@mail.ru)

Using the methods of continuous geophysical monitoring (seismic, seismic acoustic) can be detected in the rock mass dynamic (seismic) lesions of the critical deformations and their relaxation (rock bumps, outbursts, collapse of roof rocks in mine workings, etc.). To identify the listed events in the automated control of geomechanical state of rock mass is developed Multifunctional control system of gas-dynamic and geodynamic condition of rock mass. Seismic sensors placed in such a way to control the space conducting cleaning and preparatory operations. Seismic acoustic sensors mounted on the roadway in front of production face at a distance of the daily movement of mining.

The data on seismic and seismic acoustic emissions are pre-processed. They are filtering, scaling, sorting. Detected seismic and acoustic signals in real time for each channel of each sensor. Determined amplitude, spectral, frequency and energy characteristics of the signals. On the identified signals determined by the coordinates of the focus range-difference method and calculates its energy.

To forecast the risk of dynamic phenomena in a coal seam is a spatial grouping of identified "hot spots" based on their energies and zones of seismic and seismic acoustic activity. Calculates the time and the place of possible adverse events. Determined by taking into account their location, the impact on the safety of mining operations on the production floor.

GEOINFORMATIC MAINTENANCE OF SAFETY OF UNDERGROUND MINING  
OF SHALLOW COAL SEAMS

*V. V. Melnik*<sup>1</sup>, *V. N. Fryanov*<sup>2</sup>, *Y. N. Kuznetsov*<sup>1</sup>

<sup>1</sup> The National University of Science and Technology MISiS (NUST MISiS, Russia)

<sup>2</sup> Siberian State Industrial University (SSIU, Russia)

[mamu-prpm@yandex.ru](mailto:mamu-prpm@yandex.ru)

Technical and economic indicators in the Russian mines significantly worse than in the USA and Australian mines. Scientist were and practice explain this complicated in comparison with foreign mines mining and geological and mining conditions of occurrence of coal seams on the fields of Russia, namely a variable angle of dip within a single excavation site, the tendency of the majority of coal mining seams to shocks and sudden outbursts coal (rock) and gas; propensity to spontaneous combustion of coal seams; availability of coal mass thicker formations coal contiguous layers, improvement of which leads to the formation of high pressure areas of mining, gas reservoirs in the area of displacement and undermined above developed rock formation flooded developed spaces in the upper layers of waste and others.

In this paper we developed a model and software predict the likelihood of pre-emergency situations, the regularities of the formation of zones of increased fracturing and gas reservoir under the influence of clearing out space, offers recommendations to prevent dangerous situations.

Fundamentally new are the results of studies of the effect of non-uniform moving face on the intensity of rock pressure and dynamic allocation of methane-air mixture in the mine workings in production areas that are essential to ensure a safe technology of underground coal mines to Russian.

#### References

1. V. N. Fryanov, L. D. Pavlova. Status and development trends of safe technology of underground coal mining // Siberian State Industrial University. 2009. - 238 p.
2. F. N. Voskoboev, A. V. Dzhigrin, V. I. Klishin., N. M. Kachurin, V. V. Melnik. Technological solutions for active management of geomechanical processes in coal mines // Tula: Tula State University. 2015. - 458 p.
3. V. V. Melnik, V. N. Pavlysh, S. S. Grebenkine. Geomechanical substantiation of rational technological solutions for managing the state of the rock mass in underground coal mining // Donetsk "VIC". 2015. - 327 p.
4. S. S. Grebenkine, V. I. Bondarenko, V. N. Pavlysh, I. A. Ilyashev, V. V. Melnik. Scientific and technological bases of management of the state of the rock mass. // Donetsk "VIC". 2013. - 515 p.

## CONTROLLED MAGNETIC ANOMALY APPLICATION IN TECHNOLOGY

*L. A. Vaisberg*

REC “Mekhanobr-tehnika” (Russia)

[vaisberg\\_la@npk-mt.spb.ru](mailto:vaisberg_la@npk-mt.spb.ru)

From the earliest times, mankind has been learning how to generate artificial magnetic anomalies, control them, and apply for separation of magnetic and non-magnetic materials in various physical states. E.g. the processes of magnetic beneficiation based on the differences in magnetic properties of the components being separated are extensively used in the processing of ferrous, non-ferrous, and rare metal ores, strong magnetic weighting-materials recovery, removal of ferric inclusion from various materials, processing of industrial wastes and secondary raw materials. Apart from utilization in magnetic separation (generation of the magnetic field), directly in the minerals processing, magnetic materials are being widely used in other industries as well. Specifically, Magnetic Resonance Imagery (MRI) and magnetotherapy find their applications in medicine, along with whole blood magnetic cell separation, bone marrow samples and mononuclear suspension separation. It is reasonable to suggest that the set of magnetic technologies utilized currently will continue its growth with the scientific progress.

### References

1. Minerals processing desk book. Basic processes / edited by O. S. Bogdanov, 2-nd edition // Moscow: Nedra. 1983. P. 381.
2. Vaisberg L. A., Demidov I. V., Ivanov K. S. Mechanics of granular media under vibration action: the methods of description and mathematical modeling // Obogashchenie Rud. 2015. No. 4. pp. 21–31

EXPERIENCE OF USE OF THE AUTOMATED LINEAMENTARY ANALYSIS  
OF SPACE IMAGES FOR STUDYING OF MODERN GEODYNAMICS

V. N. Zakharov<sup>1</sup>, A. V. Zverev<sup>2</sup>, A. T. Zverev<sup>2</sup>, V. A. Malinnikov<sup>2</sup>, O. N. Malinnikova<sup>1</sup>

<sup>1</sup>Institute of Comprehensive Exploitation of Mineral Resources

Russian Academy of Sciences (IPKON RAS),

<sup>2</sup>Moscow State University of Geodesy and Cartography (MIIGAiK),

[olga\\_malinnikova@mail.ru](mailto:olga_malinnikova@mail.ru)

For the engineering-geological characteristic of sites of city, road and underground constructions the complex of studies including surveying, prospecting and test-field and laboratory works is carried out. The special attention is paid to remote methods for studying the jointing, durability, deformability, a tension of rocks and negative engineering-geological processes use allowing the authors to obtain essentially new engineering-geological information.

For geodynamic division into blocks and identification of a block structure of the crust the method of the lineamentary analysis of space images, namely, the schemes of roses charts of local lineament (strokes) of different ranks obtained at different sizes of the sliding window has been used.

Roses charts of similar drawing are characteristic of uniform blocks. Change of drawing happens when crossing the morphostructural lineament separating heterogeneous blocks. The intense deformed condition of blocks of the crust has been estimated according to the schemes of the density of lineament (strokes). Zones of the increased density of lineament are connected with stretching conditions, and the lowered compression. The forecast of earthquakes is carried out in the lineamentary analysis of the space images obtained for several months prior to the beginning of and after an earthquake. Before an earthquake the form of roses charts naturally changes and the value of the relation of lengths of lineament of different directions. The ways of migration of fracture waters are determined by the existence of zones of the increased density of lineament (strokes) focused across river valleys. The forecast of a landslide hazard is carried out by the existence of zones of migration of the fracture waters connected with their release in the valleys of rivers.

The enhancement of seismicity induced by industrial activity in Russia in the conditions of present-day anthropization is noted. In particular, the growth in the intensity and number of strong tectonic earthquakes with magnitudes  $M \geq 3$  (seismic energy 109 J) due to human activity is revealed. These man-made tectonic earthquakes have started to occur in the regions of the East European Platform which were previously aseismic. The development of such seismicity is noted in the areas of intense long-term mineral extraction due to the increasing production depth and extended mining and production. Induced earthquake, rock burst, Earth's crust blocks, critical stress state, focus zone, fault reactivation. DOI: 10.17580/gzh.2016.12.03 2. Adushkin V. V. Technogenic tectonic seismicity in Kuzbass. Russian Geology and Geophysics. 2018. Vol. 59, No. 5. pp. 571-583. 3. Lasocki S., Orlecka-Sikora B., Mutke G., Pytel W., Rudzinski L. A catastrophic event in Rudna copper-ore mine in Poland on 29 November, 2016: what, how and why. 30. Lovchikov A. V. Behavior of tectonic rockbursts and induced earthquakes in mines in Russia. Prediction and Prevention of Tectonic Rockbursts and Earthquakes: Measurement of Strains and Residual and Effective Stresses in Rocks. I International Symposium Proceedings. Bishkek : NAN KR, 2016. pp. 39-49. Upgrowth of strong induced tectonic earthquakes in conditions of technogenic loading accumulation. V. V. Adushkin. Institute of Geosphere Dynamics (IDG RAS). adushkin@idg.chph.ras.ru. Analysis of upgrowth of technogenic-induced seismicity of Kuzbass territory, intensive rise of that begins in 70th-80th of the last century and finalized in conditions of permanently growing technogenous loading by Bochata catastrophic earthquake of 18 June 2013 ( $M=5.8-6.1$ ), are presented in the paper too. The main opinion is devoted to the upgrowth of strong technogenic-tectonic earthquakes of trigger character having energetic scale of  $K > 8.5-9$  and magnitude of  $M > 3$  consequently. Before getting to gradient accumulation, let's start with your question: Finally to my question: what exactly happens 'under the hood'? Every operation on tensors is tracked in a computational graph if and only if one of the operands is already part of a computational graph. When you set `requires_grad=True` of a tensor, it creates a computational graph with a single vertex, the tensor itself, which will remain a leaf in the graph. Any operation with that tensor will create a new vertex, which is the result of the operation, hence there is an edge from the operands to it, tracking the operation